Glittering product range for exacting requirements.

The new GG-S gold scales and CG-S carat scales offer extremely powerful performance, dependability and convenience in the demanding, diverse application areas of the jewelery industry.

Extremely high weighing dependability for top grade weighing samples thanks to fully automatic, temperature-controlled internal adjustment (**FACT**).

Convenient and rapid access even with large containers thanks to a spacious draft shield with wide openings.

METTLER TOLEDO

Top models for highly exacting requirements

- Clear, easily understandable operation
- Rapid and dependable results
- Easily readable display
- Fully automatic adjustment
- Latest, resilient weighing technology
- Rugged, resistant construction
- Spacious, functional draft shield







Model (Order Nº)	Readability	Maximum capacity	Repeatability (*s*)	Linearity	External dim. (w x d x h) cm	Weighing pan mm
GG4002-S	0.01 g	4100 g	0.008 g	±0.02 g	23 x 10 x 36	165x165
GG4002-S DeltaRange	0.01/0.1 g	800/4100 g	0.008/0.03 g	±0.02/0.03 g	23 x 10 x 36	165x165
GG6002-S New	0.01 g	6100 g	0.01 g	±0.02 g	23 x 10 x 36	165x165
CG2502-S	0.01 ct/0.01 g	2550 ct/510 g	0.04 ct/0.008 g	±0.01 ct/0.002 g	23 x 37 x 36	128 x 128
CG13002-S	0.01 ct/0.01 g	13550 ct/2710 g	0.04 ct/0.008 g	±0.03 ct/0.006 g	23 x 37 x 36	128 x 128
CG1003	0.001 ct/0.001 g	1050 ct/210 g	0.5 mct/0.1 mg	±1 mct/0.2 mg	21 x 33 x 31	∅ 85

Standard equipment for all models
- FACT, fully automatic, temperature-controlled internal adjustment
- VariCal, adjustment with variable, external weights
- Below-the-balance weighing device
- In-use cover, replaceable
- Integrated, short-form operating instructions

GG-S, CG-S models
- Fluorescent display
- Analog capacity display
- RS232C interface
- High draft shield (CG-S)

CG1003 model
- LCD
- LocalCAN universal interface (LC option)
- Draft shield with left/right operation

All models can
- be adapted to unstable surroundings
- display the weight in 14 different weighing units
- allow selection of decimal places for faster weighing

Optional equipment
- LC-P Density printer
- Density kits
- LC-P45 normal paper printer
- All-purpose glass draft shield, low (GG-S)
- High draft shield with sliding doors (GG-S)
- Auxiliary displays LC-AD*, LC-ADS*
- LC option (GG-S, CG-S)
- External battery pack

*requires LC option

Quality certificate ISO 9001
Environment certificate ISO14001
Internet: http://www.mt.com
Worldwide service

Subject to technical changes
© 02/2001 Mettler-Toledo GmbH
Printed in Switzerland 11795128
MCG MarCom Greifensee